

THE STEERING OIL TUBE AND WIRE HARNESS ARE ARRANGED INDEPENDENTLY



PRODUCT FEATURE

- (1) Drivelines: Cummins 6.7 engine or Wuxi diesel engine meeting national level 3 (EU3) emission standard is assembled on the truck. This model possesses strong drive power and good weather-resistance.
- (2) Transmission: The model is assembled with originally designed Heli automatic transmission with a market inventory of 500, which is safe and reliable, and easy to maintain.
- (3) Drive axle: The truck is assembled with axle specially designed for heavy trucks, , stable and reliable braking, have a good using the performance ,performance and price rate
- (4) Hydraulic system: Italian hydraulic system with high efficiency and fuel economy is assembled on the truck. Advanced techniques such as load sensing and dual pump converging are applied to save energy and reduce the cost.
- (5) High strength structure components: Heavy-duty box-type chassis is reliable. The design perfectly meets the requirement of reliability and stability, especially in paper industry and container transportation.
- $\hbox{ (6) Tilting cabin makes a better experience of maintenance and repairing. } \\$

THE MAIN PARAMETER

Model		Units	CPCD150-WX-06III	CPCD160-WX-06III
			CPCD150-CU-06III	CPCD160-CU-06III
Load center		mm	600	
Lifting capacity		kg	15000	16000
Lifting height		mm	3000	
Lifting speed (at rated load)		mm/s	330	
Lowering speed (unloaded)		mm/s	300-600	
Mast tilt (forward/backward)		Grad	6月12日	
Engine			Wuxi diesel /Cummins	
Dimensions	Overall length(with fork)	mm	4735 (6105)	
	Overall width	mm	2560	
	Mast height (retracted)	mm	3220	